



# D801 Push-Lok Hose

## Section A

### Hose

Hydraulic Hose A1

Metallic Hose A2

Thermoplastic A3

Industrial Hose A4

R14 TEFLON HOSE

R14 CONVOLUTED TEFLON

MULTIPURPOSE HOSE

OIL SUCTION & DELIVERY

2SN JET WASH HOSE

AIR BRAKE HOSE

**PUSHLOCK HOSE**

Hose Protection A5

## Section B Hose Fittings

## Section C Quick Release Couplers

## Section D Adaptors

## Section E Steel Tube & Fittings

## Section F Brass Fittings

## Section G Components

## Section H Machinery

### PUSH-LOK HOSE SAE J 517 100 R6 EN 854

#### HOSE CONSTRUCTION

##### INNER TUBE

Hydraulic Oil Resistant  
Synthetic Rubber

##### REINFORCEMENT

High Tensile Synthetic  
Textile Braid

##### COVER

Oil, Abrasion, Ozone & Weather  
Resistant Synthetic Rubber

##### TEMPERATURE RANGE

(MEDIUM) -40°C to +100°C

##### APPLICATION

Push-On compatible applications

##### SAFETY FACTOR

4:1

HOSE BRAND



#### BRANDING



Part No.	Hose Size		I.D.		O.D.		Working Press		Burst Press		Bend Rad	Weight
	mm	inch	mm	mm	bar	psi	bar	psi	mm	kg/m		
D801-04	6	1/4	6.4	12.2	20	290	80	1160	76	0.14		
D801-05	8	5/16	7.9	14.1	20	290	80	1160	76	0.17		
D801-06	10	3/8	9.53	15.4	20	290	80	1160	76	0.20		
D801-08	12	1/2	12.7	18.9	20	290	80	1160	127	0.23		
D801-10	26	5/8	15.88	22.8	20	290	80	1160	150	0.32		
D801-12	19	3/4	19.0	26.0	20	290	80	1160	180	0.39		

\*Available in Grey & Black

\*Please specify colour when ordering