



# DIN 2353 - Tube Fittings

## Male Stud Connectors



**GE-R**

**BSP STRAIGHT MALE STUD COUPLER**

Part No.	Thread		Pressure Bar	Weight kg/100 pz	Series L/S
	Size (mm)	T1 T2			
<b>GE06LR-1/8</b>	6	12x1.5 1/8	315	2.5	L
<b>GE06LR-1/4</b>	6	12x1.5 1/4	315	3.5	L
<b>GE06LR-3/8</b>	6	12x1.5 3/8	315	5.6	L
<b>GE08LR-1/8</b>	8	14x1.5 1/8	315	3.1	L
<b>GE08LR-1/4</b>	8	14x1.5 1/4	315	4.5	L
<b>GE08LR-3/8</b>	8	14x1.5 3/8	315	6.0	L
<b>GE10LR-1/8</b>	10	16x1.5 1/8	315	4.0	L
<b>GE10LR-1/4</b>	10	16x1.5 1/4	315	4.7	L
<b>GE10LR-3/8</b>	10	16x1.5 3/8	315	6.0	L
<b>GE10LR-1/2</b>	10	16x1.5 1/2	315	9.2	L
<b>GE12LR-1/4</b>	12	18x1.5 1/4	315	6.1	L
<b>GE12LR-3/8</b>	12	18x1.5 3/8	315	6.5	L
<b>GE12LR-1/2</b>	12	18x1.5 1/2	315	9.5	L
<b>GE15LR-3/8</b>	15	22x1.5 3/8	315	9.7	L
<b>GE15LR-1/2</b>	15	22x1.5 1/2	315	11.5	L
<b>GE15LR-3/4</b>	15	22x1.5 3/4	315	16.1	L
<b>GE18LR-1/2</b>	18	26x1.5 1/2	315	13.0	L
<b>GE18LR-3/4</b>	18	26x1.5 3/4	315	17.3	L
<b>GE28LR-3/4</b>	28	36x2 3/4	160	25.6	L
<b>GE28LR-1</b>	28	36x2 1	160	25.0	L
<b>GE35LR-1</b>	35	45x2 1	160	37.8	L
<b>GE35LR-11/4</b>	35	45x2 11/4	160	41.0	L
<b>GE08SR-1/4</b>	8	16x1.5 1/4	630	6.0	S
<b>GE10SR-3/8</b>	10	18x1.5 3/8	630	9.0	S
<b>GE12SR-1/4</b>	12	20x1.5 1/4	630	9.3	S
<b>GE12SR-3/8</b>	12	20x1.5 3/8	630	10.2	S
<b>GE12SR-1/2</b>	12	20x1.5 1/2	630	13.5	S
<b>GE16SR-3/8</b>	16	24x1.5 3/8	400	15.3	S
<b>GE16SR-1/2</b>	16	24x1.5 1/2	400	16.0	S
<b>GE16SR-3/4</b>	16	24x1.5 3/4	400	22.6	S
<b>GE20SR-1/2</b>	20	30x2 1/2	400	24.3	S
<b>GE20SR-3/4</b>	20	30x2 3/4	400	27.0	S
<b>GE20SR-1</b>	20	30x2 1	400	41.5	S
<b>GE25SR-3/4</b>	25	36x2 3/4	400	46.5	S
<b>GE25SR-1</b>	25	36x2 1	400	49.0	S
<b>GE30SR-1</b>	30	42x2 1	400	57.8	S
<b>GE30SR-11/4</b>	30	42x2 11/4	400	82.0	S
<b>GE38SR-11/2</b>	38	52x2 11/2	315	92.0	S

